



SHAPE H, SH

Flame



Cutting data	Movie
765	


Tool No.	Art.	d1	l2	d2	l1	brazed	solid
SH-41M	24553	3.0	6.3	3.0	38.0		✓
SH-41ML2	27903	3.0	6.3	3.0	50.0		✓
SH-41ML3	27928	3.0	6.3	3.0	75.0		✓
SH-53M	24603	5.0	9.5	3.0	38.0		✓
SH-2M	24403	8.0	19.0	6.0	64.0	✓	
SH-2ML6	26703	8.0	19.0	6.0	169.0	✓	
SH-5M	24428	12.7	32.0	6.0	76.0	✓	
SH-5ML6	26728	12.7	32.0	6.0	182.0	✓	
*SH-6M	24453	16.0	36.0	6.0	80.0	✓	
*SH-7M	24503	19.0	41.0	6.0	85.0	✓	

*8 mm shanks optional



SHAPE L, KEL, SL

Ball nosed cone



Cutting data	Movie
765	

Tool No.	Art.	d1	l2	d2	l1	brazed	solid	α°
SL-41M	25403	3.0	9.5	3.0	38.0		✓	8°
SL-42M	25428	3.0	12.7	3.0	38.0		✓	8°
SL-42ML2	27953	3.0	12.7	3.0	50.0		✓	8°
SL-42ML3	27978	3.0	12.7	3.0	75.0		✓	8°
SL-53M	25453	5.0	12.7	3.0	38.0		✓	14°
SL-1M	25178	6.0	16.0	6.0	50.0		✓	14°
SL-1ML6	26753	6.0	16.0	6.0	171.0		✓	14°
SL-2M	25203	8.0	22.0	6.0	70.0	✓		14°
SL-3M	25228	9.6	30.0	6.0	74.0	✓		14°
SL-3ML6	26778	9.6	30.0	6.0	182.0	✓		14°
SL-4M	25253	12.7	28.0	6.0	76.0	✓		14°
SL-4ML6	26803	12.7	28.0	6.0	183.0	✓		14°
*SL-5M	25278	16.0	30.0	6.0	77.0	✓		14°
*SL-7M	25353	19.0	38.0	6.0	85.0	✓		14°

*8 mm shanks optional

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11